

**We empower sustainable businesses.**

## **UCON TP**

**Cubic IBC with frame for liquids**

### **Advantages:**

- Excellent stability
- Best residual emptying
- Protected inner tank due to stable transport frame
- High stability due to additional cross bracing
- Crane openings in the frame supports for attaching crane gear or crane hooks
- Welded tank feet guarantee even weight transfer of the filled container to the frame
- Environmentally friendly



### **Industries:**

**FOOD | CHEMICALS | PHARMACEUTICALS | PLASTICS | COATINGS**

### **Unbeatable lifetime.**

**UCON, the safe choice.**

The UCON TP combines optimum cleaning geometry, best residual emptying and non-permeation. The wear-free design allows long-term reusable use. Thanks to the variety of sizes and the possibility of using different types of stainless steel, the TP meets all your requirements. Our unerring pursuit of quality and perfection guarantees you maximum safety and durability. Your requirements and our pioneering culture result in customized, innovative stainless steel products.

**UCON Container System GmbH**

[www.uconcs.com](http://www.uconcs.com) | [info@uconcs.com](mailto:info@uconcs.com)

Gustav-Rivinius-Platz 2 | D-77756 - Hausach – Germany | +49 7821 77 0 |  
Amtsgericht Freiburg HRB 715155 | Umsatzsteuer-ID: DE 112 589 766 |  
Geschäftsführung: Igor Ferlan, Ulrich Lauster

**We empower sustainable businesses.**

# Environmentally friendly IBC for liquids

Type TP. The stainless steel construction guarantees the longest possible lifetime.

## Area of application:

- Transportation and storage of raw materials and products in the pharmaceutical, chemical, paint, plastics and food industries
- Transportation of hazardous substances in accordance with ADR, RID and IMDG (UN approval)
- Aseptic design on request

## Certifications:

- UN approval
- As collection or removal container according to TRbF20.

## Versions:

- - TPN the more cost-effective "light version"
- - TPO without frame

## Advantages:

- Fire-resistant for 30 minutes with screw-on lid.
- Rubber buffers serve as vibration dampers and for decoupling between tank and transport frame
- Potential equalization between tank and protective frame through earthing strap
- Drive-in protection plates on 4 sides to protect the outlet and outlet fittings
- Optimum utilization of space

## Volume:

445 - 1250 Liter

## Handling:

- Suitable for crane
- Stackable

TYPE	Volumen Liter	Max. External Dimensions			Max. Weight	Max. Density
		Breite	Länge	Höhe	Kg	Kg/l
TP 445	445	832	1032	1165	135	1,50
TP 500	500	832	1032	1290	150	1,50
TP 500	500	1022	1222	1140	170	1,85
TP 800	800	1022	1022	1405	190	1,85
TP 1000	1000	1022	1222	1650	210	1,85
TP 1250	1250	1022	1222	1865	235	1,60

*\*Further basic dimensions and volumes on request.*



MADE IN GERMANY

**UCON Container System GmbH**

[www.uconcs.com](http://www.uconcs.com) | [info@uconcs.com](mailto:info@uconcs.com)

Gustav-Rivinius-Platz 2 | D-77756 - Hausach – Germany | +49 7821 77 0 |  
 Amtsgericht Freiburg HRB 715155 | Umsatzsteuer-ID: DE 112 589 766 |  
 Geschäftsführung: Igor Ferlan, Ulrich Lauster